



BAUER I-SERIES 5

Water-Cooled Designed for High-Flow Applications

Self-contained transportable helium system configured for plug-and-play operation with easy site setup. Flexible inlet pressure range from 5 to 215 PSIG.

SYSTEM FOOTPRINT

DIMENSIONS L x W x H feet (mm)

› 40' x 8' x 9.5'

(12192 mm x 2438 mm x 2895 mm)

WEIGHT pounds (kg) approx.

› 22700 lbs (10297 kg)

TECHNICAL DATA

Model	Max Inlet Pressure		Capacity FGD		RPM	Number of Stages	Motor		Drive
	PSIG	BAR	SCFM	M ³ /HR			HP	KW	
UP TO 5000 PSIG									
GRU & IB23.12 (XXL)	15	1	116	157	1500	5	85-100	64-75	E3
GRU & IB26.12 (XXL)	15	1	367	520	1500	5	250-275	187-205	E3
GRU28 & IB52.12 (XXL)	15	1	766	1044	1500	5	485-535	362-399	E3



BAUER CONNECT®

IOT REMOTE TELEMETRY AND CONTROL

BAUER CONNECT® is an app and internet-based IoT solution that allows BAUER customers to remotely monitor - and control - the performance of the entire BAUER system through any wireless mobile device or computer; anytime, anywhere.

Key Features: allow customers to increase efficiency and productivity, save time, do more with fewer resources, enjoy lower operational costs, and have total flexibility with a solution tailored specifically for the end-user.

BAUER CONNECT® - Connection that matters.

TO LEARN MORE VISIT

bauer-connect.com

FOR MORE INFORMATION PLEASE CONTACT:

U.S. HEADQUARTERS:

BAUER COMPRESSORS, INC.

1328 Azalea Garden Road
Norfolk, VA 23502

Tel. +1 (757) 855-6006

Fax +1 (757) 857-1041

IndustrialSales@bauercomp.com

www.BauerComp.com



1171.08.24

Subject to technical changes